


Intercom/Broadcast Module Specification

X20 Pro

This product can be widely used in public emergency places such as commerce, education, logistics, medical treatment, high-speed, barrier and so on.



Specification

CPU: DVF97187

Memory (Flash/RAM) : 128M

LED: LED lamp*1

Audio codec: G.722, G.711 (A/μ), G.723.1, G.729AB, G.726, iLBC

Call feature: Full-duplex channel, support call forward, auto answer, one-key alarm

Package: PCBA*1

Language: English

Upgrade: TFTP/HTTP/Local upload

Protocol: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, DHCP, OPENVPN

Dimension: 75(W) * 90(L)mm

Working Temperature: -30°C ~ 70°C

Operating humidity: 10% to 95% non-condensing

Interface

Button*3, 4pin 1.25mm

Input*2 10pin 2.54mm

Handset*1 4pin 1.25mm

Numeric keypad*1 10pin 1.25mm

LCD*1 10pin 1.25mm SPI

MIC*1 2pin 1.25mm

Speaker*1 2pin 1.25mm power: 3W

Reset button*1

IP check button*1

External amplifier*1 3pin 1.25mm

Active output*1: 12-24V 2pin 1.25mm

Power supply*1: 12V-24V DC

Network: 1*LAN RJ-45 10/100M (support POE)